



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

1 Identification

- · Product identifier
- · Trade name: Type X Gypsum Board
- Other product identifiers:

5/8" Abuse Resistant Type X

5/8" CertainTeed Type X

5/8" Exterior Soffit Type X

5/8" Extreme Abuse Type X

5/8" Extreme Impact Type X

5/8" Sheathing Treated Core Type X

5/8" Veneer Plaster Base Type X

- · Recommended use and restriction on use
- · Recommended use: Gypsum panel products for interior and exterior wall applications.
- Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

CertainTeed Gypsum

20 Moores Road

Malvern, PA 19355

Professional: 800-233-8990

Consumer: 800-782-8777

www.certainteed.com

· Emergency telephone number:

ChemTel

(800)255-3924 (North America)

+1 (813)248-0585 (International)

1-300-954-583 (Australia)

0-800-591-6042 (Brazil)

400-120-0751 (China)

000-800-100-4086 (India)

800-099-0731 (Mexico)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: None.
- · Signal word: None.
- · Hazard statements: None.
- · Precautionary statements: None.
- Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

Trade name: Type X Gypsum Board

(Cont'd. of page 1)

· Component	ts:	
13397-24-5	Calcium sulphate	70-90%
9004-34-6	Cellulose	0-10%
9005-27-0	Starch, 2-hydroxyethyl ether	0-9%

· Additional information:

All concentrations are in percent by weight.

Raw material in this product contains respirable crystalline silica as an impurity. Independent testing of this product suggests that under most conditions of use, this product will not result in exposure to respirable crystalline silica that exceeds OSHA's Action Level, (AL) or Permissible Exposure Limit (PEL). However, actual concentrations of respirable silica may vary based on the conditions of use. Specific exposures can only be determined by workplace industrial hygiene testing.

https://www.certainteed.com/drywall/osha-crystalline-silica-techupdate-certainteed-gypsum-board-products

4 First-aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Brush off loose particles from skin.

Wash with soap and water.

Seek medical treatment in case of complaints.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Coughing

Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: None.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

Trade name: Type X Gypsum Board

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Cont'd. of page 2)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Do not breathe dust.

- · Environmental precautions No special measures required.
- · Methods and material for containment and cleaning up

Sweep up and place into an appropriate container.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling
- Precautions for safe handling:

Prevent formation of dust.

Avoid breathing dust.

Handle with care.

- Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Storage area should be dry and well-ventilated.

Avoid storage near extreme heat, ignition sources or open flame.

- Information about storage in one common storage facility: Protect from humidity and water.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

13397-24-5 Calcium sulphate		
REL (USA)	Long-term value: 10* 5** mg/m³ *Total dust; **Respirable fraction	
TLV (USA)	Long-term value: 10* mg/m³ *as inhalable fraction	
EL (Canada)	Short-term value: 20* mg/m³ Long-term value: 10* 3** mg/m³ *total dust; **respirable fraction	
EV (Canada)	Long-term value: 10 mg/m³	

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

Trade name: Type X Gypsum Board

		(Cont'd. of page 3)
	inhalable	
LMPE (Mexico)	Long-term value: 10* mg/m³ *inhalable fraction	
9004-34-6 Cellu	lose	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	Long-term value: 10 mg/m³	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction	
EV (Canada)	Long-term value: 10 mg/m³ paper fibre, total dust	
LMPE (Mexico)	Long-term value: 10 mg/m³	

- Exposure controls
- · General protective and hygienic measures: Avoid breathing dust.
- Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Use respiratory protection when grinding or cutting material.

Particulate mask should filter at least 99% of airborne particles.

· Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear gloves for the protection against mechanical hazards according to OSHA and NIOSH rules.

- Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties

Information on basic physical a	and chemical properties	
· Appearance:		
Form:	Solid	
Color:	White	
· Odor:	Odorless	
· Odor threshold:	Not determined.	
· pH-value:	Not applicable.	
· Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Product is not flammable.	
· Auto-ignition temperature:	Not determined.	
		(Cont'd. on page 5)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

Trade name: Type X Gypsum Board

		(Cont'd. of page
Decomposition temperature:	1450 °C (2642 °F)	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
Vapor pressure:	Not applicable.	
Density:		
Relative density:	Not determined.	
Vapor density:	Not applicable.	
Evaporation rate:	Not applicable.	
Solubility in / Miscibility with		
Water:	Insoluble.	
Partition coefficient (n-octanol/water):	Not determined.	
Viscosity		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: The product is non-reactive under normal conditions of use, storage and transport.
- · Chemical stability: Stable under normal temperatures and pressures.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Moisture.
- · Incompatible materials No relevant information available.
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Sulfur oxides (SOx)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- Sensitization: Based on available data, the classification criteria are not met.

(Cont'd. on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

Trade name: Type X Gypsum Board

(Cont'd. of page 5)

· IARC (International Agency for Research on Cancer):

14808-60-7 Quartz (SiO2)

1

· NTP (National Toxicology Program):

14808-60-7 Quartz (SiO2)

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Eye contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

This product contains crystalline silica (quartz) as a naturally occurring impurity. The International Agency for Research on Cancer (IARC) and the National Toxicology Program classify respirable crystalline silica as known human carcinogens. Independent testing of this product suggests that under most conditions of use, this product will not result in exposure to respirable crystalline silica that exceeds OSHA's Action Level, (AL) or Permissible Exposure Limit (PEL). Exposures to respirable crystalline silica at or above the OSHA AL, or PEL are not expected during the recommended use of this product. However, actual concentrations of respirable silica may vary based on the conditions of use. Specific exposures can only be determined by workplace industrial hygiene testing.

- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

(Cont'd. on page 7)

Page: 7/8

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

Trade name: Type X Gypsum Board

(Cont'd. of page 6)

Transport information		
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· UN proper shipping name · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
· DOT, ADR/RID/ADN, IMDG, IATA · Class	Not regulated.	
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· Environmental hazards · Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

(Cont'd. on page 8)

Page: 8/8

1

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 02, 2020

Trade name: Type X Gypsum Board

(Cont'd. of page 7)

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

14808-60-7 Quartz (SiO2)

Canadian Domestic Substances List (DSL):

All:

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com